


ABRASION DEBRANNER VTA20



Application

The Satake Debranning Machine Type VTA is a high capacity machine designed for removing the outer bran and husk layers from cereals such as wheat, barley and rye by abrasion. The machine is exceptionally hard wearing and is designed for trouble free 24 hour production.

Operating Principle



The stock enters the VTA via a regulator valve and into the milling chamber. The product works its way between the vertical abrasive stones, resistance bars and screen. An exhaust connection on the machine pulls removed bran and dust through the screens and onwards to be collected in a cyclone or dust collector. The degree of milling is controlled by a weighted outlet gate and can be adjusted in seconds.

Option

Milling degree can be PLC controlled by an 'Autoweight' system fitted to the outlet gate.

Combination

The machine can be used as 'stand alone'. For very high debranning rates, the VTA can be used before the VCW PeriTec unit or in series.




Motor: 75 - 110 kW 6 Pole

Required Exhaust: 80m³/minute at 1.0 ~ 1.5 kPa

Weight Without Motor: 1,800 kg approx.

All Satake products are the subject of continuous development and, as a result, their specification may change and differ in detail from that outlined in this leaflet.



SATAKE AUSTRALIA Pty Ltd
15 Leland Street
Penrith
NSW 2750
Australia

Telephone: +61 (0) 2 4725 2600
Facsimile: +61 (0) 2 4725 2601
E-mail: info@satake.com.au
Website: www.satake.com.au